



iCON 2055 Wi 4G

Reference: 10130
EAN13: 8427338101308


- **Inverter** from **200Amp to 60%**.
- Equipped with **welding accessories** .
- Valid for **generator** .
- **TIG by Lift-Arc**.
- Front **digital** .
- Construction **antishock DDR**.
- With technologies **Geolocalization 4G, Wifi, Connect and WaaS**.



Main features:

To talk about **professional welding** is to talk from the **iCON** product line. Due to its patented and innovative **DDR** constructive design, its great capacity to work under **intensive conditions** and demanding environments, and its unmatched results in terms of reliability and performance, this is undoubtedly the best option for the most demanding professionals.

- Stability and arc control regardless of the electrode-material distance, thanks to the **ARCSENSE** regulation.
- **Double automatic ventilation** , acting only when the equipment requires it.
- **STAND-BY position** , when the equipment is not in operation.
- Equipped with **Anti-stick, Arc-Force, HotStart and Lift-Arc (TIG) devices**.
- Can be connected to **generators** with a wide range of working voltages.





CARACTERÍSTICAS TÉCNICAS

Intensity MAX.	200A
Duty cycle at 40°C	50%
Intensity at 60%(100%) 40°C	180A (120A)
Regulation	5-200A (20,2 -28V)
Usable electrodes	1,6 - 4,00 mm
Connection	230V - 1Ph
Usable range	180V - 300V
OCV	68V
Max. absorbed power	9,5Kva
I _{max}	42A
I _{eff}	29,7A
Fuse	16A
Apply for demo	0
Ventilation	DOBLE - AUTO
Weight	6,4Kg
Regulation panel	SOLTER ICON DIGITAL
Norms	EN-60974-1, EN-60974-10
Protection Index	IP23C
Tig usable electrodes	1,0 - 3,2 mm
Dimensions	430x175x325mm