

BLANKED FIRE RETARDANT 600°C 2000 x 1860 SOLTER

Ref. 10082



🔗 The **600°C Fireproof Blanket** from Solter is designed to provide **superior protection against sparks, molten metal splashes, and extreme temperatures**. Made of **fiberglass with a polyurethane coating**, it offers high resistance to fire and water, ensuring a safer and more efficient work environment. **Complies with major international standards**, guaranteeing reliability in demanding industrial environments. Protect your workspace with maximum thermal safety.

¡Ensure your protection with Solter quality!

Main Features:

- 🔗 **Advanced Thermal Protection:** Designed to withstand temperatures of up to **600°C in vertical use**, making it ideal for **welding, oxy-fuel cutting, and plasma cutting** in demanding environments.
- 🔗 **High Tensile Strength:** Its robust structure complies with **EN ISO 13934-1**, ensuring greater mechanical resistance and preventing tears in intensive work environments.
- 🔗 **Fire Spread Safety:** Thanks to its fireproof composition, it complies with **UNE EN ISO 15025**, limiting flame propagation and reducing the risk of fires.
- 🔗 **Guaranteed Waterproofing:** Its highly resistant material complies with **UNE EN 20811**, providing an effective barrier against water penetration in humid environments.
- 🔗 **Superior Thermal Insulation:** Its **ISO 9151** certification ensures excellent **protection against convective heat**, reducing thermal transfer in work areas.
- 🔗 **Safe Use in Welding and Thermal Cutting:** Certified under **EN ISO 11611**, it is a reliable option for **protection during welding processes and related techniques**, preventing damage from sparks and molten metal splashes.
- 🔗 **Trust Solter to ensure maximum safety in every welding process.** Quality, durability, and protection in a single product.

BLANKED FIRE RETARDANT 600°C 2000 x 1860 SOLTER

Ref. 10082

TECHNICAL DATA

OPTIONAL ACCESSORIES

Generals

Regulations	UNE EN 13501-1:2007+A1:2010
Product Code	10082
Use	Trabajos de soldadura, oxicorte y corte por plasma

Structural

Material	Fibra de vidrio recubierta de poliuretano, sin amianto
Dimensions	2000 x 1860 mm