SOLCUT 50

Ref. 10133





The SOLCUT 50 is a high-end plasma cutting machine, designed for professionals seeking performance, durability, and precision in every cut. With a cutting capacity of up to 12 mm in steel and aluminum, this portable Inverter unit combines power and energy efficiency in a compact and robust design. Its single-phase power supply of 230V – 1Ph makes it perfect for industrial and maintenance work. It includes a ground clamp and torch, ensuring you can start working immediately. Invest in quality and precision with the SOLCUT 50.

Main Features:

- ② Clean and flawless cuts: Thanks to its 45A power, the SOLCUT 50 delivers precise and uniform cuts, minimizing the need for rework or corrections, saving time, and improving work quality.
- ② Cutting capacity up to 12 mm: Designed to cut steel, stainless steel, and aluminum, this machine allows you to handle everything from light tasks to more demanding industrial applications without compromising efficiency.
- Inverter Technology: Its Inverter system optimizes power consumption, ensuring a stable and efficient arc, which reduces consumable wear and extends the equipment's lifespan.
- ② Portable and durable design: Weighing only 12 kg, this machine is easy to transport, making it an ideal choice for work in various environments without losing robustness or stability.
- ☑ Single-phase 230V power supply Full compatibility: Operates with standard electrical networks, eliminating the need for transformers or special installations, making it easy to use anywhere.
- ② Cooling system with forced ventilation: Prevents overheating, allowing for longer work sessions and improving performance under demanding conditions.
- ② Complete kit for immediate work: Comes with a ground clamp and torch, ensuring you can start working immediately without the need to purchase additional accessories.
- The SOLCUT 50 is synonymous with precision, efficiency, and reliability. Equip your workshop with the best plasma cutting technology.



SOLCUT 50

Ref. 10133



TECHNICAL DATA

Generals	
Intensity at 60%(100%) a 40°C	40A (32A)
Intensity MAX.	45A
Regulations	EN 60974-1, EN 60974-10
Regulation	15 - 45A
Duty Cycle at 40°C	45A @ 50%

Technical	
Cutting capacity ALUMINIUM	12mm
Cuttinh capaciity STEEL	12mm
Cutting capacity STAINLESS STEEL	8mm
Air flow	150l/min
Air pressure	3,5 -10bar
Optimal aire pressure	4,5 bar

Structural	
Dimensions	504x213x314mm
Protection index	IP21
Weight	12 kg
Ventilation	FORZADA

Electrical	
l ₁ max	23A
Absorved power max.	5Kva
Supply Voltage	230V - 1Ph
ocv	310V

OPTIONAL ACCESSORIES

Ref. 06148

CONJ. 3m Cu25mm 10-25 EARTH CLAMP 200



Ref. 55971

PT-60 / IPT-60 PLASMA TORCH

