AEROPROCESS DVW Wi















The AEROPROCESS DVW Wi is the ultimate solution for industrial welding. Designed for highdemand applications, this professional synergic multiprocess MIG welding machine features a separate wire feeder and a powerful AeroCool water cooling system to maximize efficiency in every weld. Available in 320A, 400A, and 500A versions at a 45% duty cycle, it guarantees exceptional performance on all materials including steel, aluminum, and stainless steel. Additionally, its advanced synergic control automatically optimizes parameters for a stable arc with minimal spatter, ensuring maximum precision. Thanks to the integrated Welding Intelligence (Wi) module it offers advanced connectivity, remote control, and data management for complete welding process monitoring. Take your productivity to the next level with Solter technology!

Key Features:

- ② Multiprocess welding machine: Compatible with MIG-MAG (with and without gas), TIG Lift-Arc, and MMA, adapting to any type of job.
- ☑ Intelligent synergic control: Automatically preselects the best parameters based on material and thickness, ensuring high-quality welds with optimal settings.
- **2** Stable arc with minimal spatter: Arc height regulation system that reduces spatter and enhances weld bead stability.
- ② Adjustable Crater-Filling: Ensures a perfect weld bead finish, ideal for jobs requiring aesthetics and precision.
- 2 Adjustable power: Available in 320A, 400A, and 500A models with a 45% duty cycle, ideal for prolonged welding without interruptions.
- ② Advanced consumption and cost control: Real-time voltage and current monitoring during welding, with data storage for operational cost analysis.
- **Welding wire management:** Precise control of wire consumption, enabling better planning and material optimization.
- **Storage of up to 21 custom programs:** Enables repetition of optimal settings, reducing errors and maximizing efficiency.
- ☑ Impeccable results on multiple materials: Outstanding performance on carbon steel (SG3), stainless steel (Ss-309, Ss-316), aluminum (AL-5356, AL-4043), copper-silicon (CuSi3), and flux-cored welding (Fc-Rutile, Fc-Basic, Fc-316, E71T-GS gasless).
- ② Welding Intelligence (Wi) Technology: WaaS Welding connectivity for real-time monitoring, data storage, and remote optimization.



AEROPROCESS DVW Wi





TECHNICAL DATA

OPTIONAL ACCESSORIES

Generals			
Intensity at 60% (100%) a 40°C	320A (280A) // 400A (320A) // 500A (350A)		
Intensity MAX.	320A // 400A // 500A		
Regulations	EN60974-1, EN60974-10		
Regulation	10-320A(10,4-30	10-320A(10,4-30V) // 10A-400A(10,4-34V) // 10-500A(10,4-36V)	
Duty Cycle at 40°C		40% // 40% // 35%	
Technical			
Usable wire coil		D300 - 15kg	
Usable electrodes MMA		1,6mm - 4,0mm	
Usable electrodes TIG		1,6mm - 3,2mm	
Usable welding wire		0,6 - 1,6 mm	
Motor max power		65W	
Wire feeder rolls		4R	
Wire speed		018m/min	
Structural			
Dimensions		655x275x1290mm	
Protection index		IP23S	
Regulation board	Α	AEROPROCESS SYNERGIC	
Weight		85kg	
Ventilation		TUNNEL AUTOMATIC	
Electrical			
Supply Voltage		400V - 3ph	
Fuse		16A	
Absorved power max.		15Kva // 22Kva // 23Kva	
OCV		62V	

