TUNGSTEN SHARP 750

Ref. 10350





With the **TUNGSTEN SHARP 750**, you'll achieve unparalleled precision in tungsten electrode sharpening, optimizing your welding performance. Its ergonomic and compact design, combined with a built-in dust collection system, ensures a cleaner, safer, and more efficient work environment. Adjust to the perfect angle (15°, 18°, 22.5°, or 30°), choose from 6 speed settings, and achieve a uniform tip for a stable, uninterrupted arc. The quality of TIG welding starts with a well-sharpened electrode. **Invest in quality and safety—take your welding to the next level with Solter.**

Main Features:

- Professional Precision Sharpening: Enables sharpening of tungsten electrodes from 1.6 to 4.0 mm, ensuring exact geometry for a more stable and efficient welding arc.
- ② Angle Versatility: Adjustable to 15°, 18°, 22.5°, and 30°, adapting to different welding needs while improving arc penetration and stability.
- ☑ High Power and Performance: Equipped with a 750W motor and 6 adjustable speeds, reaching up to 11,000 rpm for fast and uniform sharpening.
- ② **Dust Collection System**: Reduces exposure to tungsten particles, protecting the operator's health and keeping the workspace clean.
- ② Integrated Cutting and Grinding: In addition to sharpening, it allows for cutting and tip grinding, maximizing electrode lifespan and reducing waste.
- ☑ Ergonomic and Portable Design: Weighing only 1.6 kg and featuring compact dimensions (340x76x76 mm), it is easy to transport and store—ideal for industrial and workshop environments.
- ② Durability and Reliability: Robust construction with high-quality components, ensuring efficient and long-lasting performance with minimal maintenance.
- Trust Solter to take your TIG welding to the next level with precise, safe, and waste-free sharpening.



TUNGSTEN SHARP 750

Ref. 10350



TECHNICAL DATA

| Generals | |
|-----------------------|-------------------------|
| Product Code | 10350 |
| | |
| Technical | |
| Motor max power | 750W |
| Usable electrodes TIG | 1,6 - 4.0mm |
| Angulo de amolado | 15° - 18° - 22,5° - 30° |
| Velocidad maxima | 11000 |
| N° velocidades | 6 |
| | |
| Structural | |
| Dimensions | 340x76x76 mm |
| Weight | 1,6kg |
| | |
| Electrical | |
| Tensión Alimentación | 230V +/- 15% |

OPTIONAL ACCESSORIES

Ref. 10352

DISC TUNGSTEN SHARP 750

Ø34ext X Ø5int X 2.3mm

