

ICONTIG 2220 HF PULSE PRO

Ref. 04194



- TIG DC PULSED equipment with high frequency (HF).
- Power of 220A at 60%.
- Supplied with ground clamp set and 4m SR-17 TIG torch.

iCONTIG equipment is the best compromise between precision and power. Due to its patented and innovative DDR construction design, due to its great capacity to work under intensive conditions and demanding environments and due to its unmatched results in terms of reliability, performance and power, this is undoubtedly the best option for the most demanding professionals.

Main features:

- Stability and arc control, regardless of the electrode-material distance thanks to regulation by ARCSENSE.
- Double automatic ventilation, acting only when the equipment requires it.
- STAND-BY position, when the equipment is not in operation.
- Equipped with Anti-stick, Arc-Force, Hot-Start and Lift-Arc / HF (TIG) devices.
- Connectable to generators with a wide range of working voltage.

ICONTIG 2220 HF PULSE PRO

Ref.04194



TECHNICAL DATA

Generals

Intensity at 60%(100%) a 40°C	180A (140A)
Intensity MAX.	220A
Regulation	10-220A
Duty Cycle at 40°C	50%

Technical

Usable electrodes MMA	1,6mm - 4,0mm
Usable electrodes TIG	1,6 - 3,2mm
Frecuencia de pulsado TIG	2000Hz

Structural

Dimensions	430x175x325 mm
Protection index	IP23C
Standards	EN 60974-1, EN 60974-10
Regulation board	iCONTIG "pulse"
Weight	7,2 Kg
Ventilation	Doble / Double AUTO

Electrical

Supply Voltage	230V-1ph
Fuse	25A
Absorbed power max.	8,5KVA
Voltage range	120V - 310V
OCV	68V

OPTIONAL ACCESSORIES

Ref. 06034

PEDAL AEROTIG



Ref. 06126

CONJ. 3m Cu25mm 35-50 ELE 200A



Ref. 56246

GAS REGULATOR R25 AR/CO2



Ref. 70608

TORCH CONNECTOR SOLTER

